

# XMP-6250

1080p Solid-State Network Media Player



Embrace the multimedia age with the XMP-6250 Media Player. Feature dynamic and engaging digital signs in designed locations to deliver customized information or advertisement instantly.

## Effortless Setup

Setting up the XMP-6250 couldn't be easier. Simply power up the device and you are ready to go. Previous technology experience is not necessary, which reduces overall set up costs.



## Easy and Flexible Usability

So much power is packed into such a small form factor. The XMP-6250 content management is centralized and remote. You can control playback schedule as well as turn on and off display all from your fingertips.

## Minimal Maintenance

The robust XMP-6250 is designed for 24/7 usage with self-recovery mechanism and a fanless cooling system for minimal maintenance and maximum running time.



# Technical Specification

## Open Standards Supported

- HTML5, JavaScript, and CSS
- Android 4.4 API
- W3C SMIL for cross-platform management
- W3C Widgets for HTML delivery
- POPAI Digital Signage Content Standards, including:
  - S1 (JPEG 480p baseline)
  - S2 (JPEG 720p baseline)
  - S4 (MPEG L2 audio)
  - S5 (MP3 audio, 384Kbps)
  - S6 (MPEG-1 SIF, 3Mbps CBR)
  - S7 (MPEG-1 480p, 10Mbps CBR)
  - S8 (MPEG-1 720p, 15Mbps CBR)
  - S9 (MPEG-2 480p, 6Mbps CBR)
  - S10 (MPEG-2 720p, 12Mbps CBR)
  - S11 (H.264/MPEG-4 AVC, 480p, 6Mbps CBR)
  - S12 (H.264/MPEG-4 AVC, 720p, 10Mbps CBR)
  - E1 (PNG 24bpp+alpha, 480p)
  - E2 (PNG 24bpp+alpha, 720p)
  - E4 (VC-1/WMV9, MP@ML, 720p)
  - E7 (MPEG-4 ASP, 480p, 10Mbps CBR)
  - E8 (H.264/MPEG-4 AVC, 1080p, 20Mbps CBR)

## Advanced Signage Features

- Remote commissioning
- AlwaysOn, AppLock to prevent unauthorized access
- StrongCache for continued playback even when network is not available

## HTML5 Support

- Widgets for calendar, clock, news, weather, and web page integration
- HTML5 technologies including CSS and Javascript
- WebKit-based browser engine, same as Google Chrome™ and Apple Safari® browsers

## Digital Signage Features

- Multi-zone screen layout, transparent PNG overlay, and graphical scrolling ticker
- Auto-play starts playing scheduled contents automatically when power is re-established
- Automatic error recovery with built-in WDT
- Real-time clock with backup clock battery

## Content Management

- SignApps Express Utility
- 3rd party solution (optional license)

## Connectivity

- Wi-Fi: 802.11 b/g/n
- HDMI 1.4 (Full-HD 1080p with audio)
- Ethernet 10/100 BASE-T
- 3.5mm analog stereo audio out
- S/PDIF out
- USB 2.0 x 2
- Micro USB for ADB
- Optional 3G/4G mobile module via USB

## Local Storage

- 8 GB flash memory (approx. 360 minutes of typical 720p video @3 Mbps)
- Micro SD card slot (support up to 32GB storage)

## Mounting kit

- Built-in mounting holes 100x115(mm)

## Supplied accessories

- HDMI cable
- External 2dB Wi-Fi antenna
- Velcro

## Expansion Options

- 16GB/32GB micro SD/SDHC memory card

## AC Adapter

- Input: 100-240V, 50-60 Hz, 0.5A Max.
- Output: 12V, 1.5A
- UL/CB/PSE certified power supplies
- Interchangeable connector system includes US plugs (Option for EU, UK and AUS plugs)

## Environmental

- Operating temperature: 0 to 50°C
- Humidity: 10 to 85% @ 45°C, non-condensing

## Dimensions for Product and Package

- Size: 138.60mm x 128.10mm x 30.20mm / 5.45" x 5.04" x 1.19"
- Weight: 334.2g / 0.74lbs.
- Individual Package Size: 226mm x 172mm x 89 mm / 8.89" x 6.77" x 3.5"
- Outer Carton Size: 482mm x 390mm x 245mm / 18.97" x 15.35" x 9.64"
- Units per Outer Carton: 10

## Certifications

- CE/FCC/IC

## Warranty

- 1-year limited parts & labor

# Product Photos



Retail advertisement demo  
(Monitor not included)

# Contact

**IAdea Corporation (Headquarters)**  
 3F, No. 21, Lane 168, Xingshan Road  
 Taipei, Taiwan 114  
 Phone: +886-2-2791-1110  
 Fax: +886-2-2791-1170  
 Email: [Sales@IAdea.com](mailto:Sales@IAdea.com)  
 Website: <http://www.IAdea.com>

# Authorized Reseller



**QUANTUM SPHERE**  
GATEWAY TO EXCELLENCE

PO Box 6077  
 Dural, NSW 2158 Australia  
 P: 1300 571 188  
 E: [sales@qsphere.com.au](mailto:sales@qsphere.com.au)  
 F: 02 8569 0655  
[www.qsphere.com.au](http://www.qsphere.com.au)